Loading Protocols from an USB Flash Drive on MR750 (3T WEST)

- 1. Insert **USB flash drive** into the console computer.
- 2. Open **Image Management Database** window, and click on **Protocol Exchange** in Data Apps.

		8	— ———							
ource:	Local DB	-					0	1	Session Apps	
				6					Viewer	
# Exan	ns: 24	elect:	-	Find: Name				×	Multi-Exam Viewer	
xam	Station name	Name	Date 🔻	Description	Modality	Archived	Transferred	d		- 12
250	MROW2	ARIA-6014-1	04 16 2010		MR	No	No		FlowAnalysis	
249	MROW2	no_name_249	04 16 2010		MR	No	No			
248	MROW2	no_name_248	04 16 2010		MR.	No	No		Functool	
247	MROW2	test, test	04 16 2010		MR	No	No			
246	MROW2	no_name_246	04 16 2010		MR	No	No		ClariView	
245	MROW2	Eyler_train	04 16 2010		MR	No	No			
244	MROW2	bnm	04 16 2010		MR	No	No	-	Data Apps	
# Sari	os: 10 Si	elect:					ſ	×	Data Export	
Series 🛦	Туре	Images	Description	Modality	Manufacturer	Archived on	Transferred to		SR Viewer	
	PROSP			MR	GE MEDICAL SYS					
2	PROSP	168	FSPGR_SAG_TI550	MR	GE MEDICAL SYS				ProtoCopy	
3	PROSP	7712 BART_ramp MR GE MEDICAL SYS								
4	PROSP	128	fm_TE1_NFS	MR	GE MEDICAL SYS				ProtocolExchange	
5	PROSP	128	fm_TE2_NFS	MR	GE MEDICAL SYS					
			Construction of the second second						SACE	A 198

3. Choose Import Mode

	Mode Selection
PI	lease select mode:
0	Export Mode
۲	Import Mode
	OK Cancel

4. In the Protocol Exchange screen, click the + sign next to USB to expand the list of protocols. Click the protocol to be imported and drag it to the Protocol Selection (right panel). Highlight the protocol, and click **Import.**

Protocol Source	Protocol Selection	
USB USB aduit Brad FinnLBasic FinnLAdvanced	••• FMRI_Basic	Preferences Preview Import Refresh To Export Mode
Import protocol to system success.		
		Quit

5. A **password window** pops up. You do NOT need to type in a password. Click OK. The progress bar at the bottom moves left to right indicating transferring. Wait till after the message "Import protocol to system success" displays, click **Quit** to exit Protocol Exchange.

Note: If an "incompatible hardware" error occurs after clicking OK in the password window, It means that the protocol is not supported by the system. Even though "Import protocol to system success" may still display, the protocol will not be loaded onto the system.

6. Make sure that the light on the USB flash drive is not blinking, and then unplug the USB flash drive.